

**REMARKS**

Claims 1-33 are pending. By this Amendment, a Substitute Abstract is submitted; a Substitute Specification is presented; Figures 17-19(B) are amended; and Claims 1-33 are amended. As the claims are amended primarily to address informalities therein, and because support for the additional feature(s) added to Claim 1 herein by amendment is provided in the application as originally filed, Applicant respectfully submits that no new matter is presented herein.

**IN THE DRAWINGS;**

Figures 17-19(B) are objected to for not being labeled with a --Prior Art-- legend because only that which is old is illustrated therein. Applicant has responded to the objection by amending Figures 17-19(B) to include a --Prior Art-- legend. Withdrawal of the objection is respectfully requested.

**ABSTRACT:**

The Abstract of the disclosure is objected to for containing improper language and for not being in proper format. Enclosed herein is a Substitute Abstract that is believed to be responsive to the objection. A marked up copy of the originally filed Abstract is also presented herein indicating the changes made thereto. Applicant respectfully requests withdrawal of the objection.

**SPECIFICATION:**

The Office Action objects to the originally filed Specification and requires a Substitute Specification, excluding the claims, be submitted due to the presence of grammatical errors and awkward syntax in the originally filed Specification. Enclosed herein is a Substitute Specification addressing the stated basis of the objection.

Applicant has amended the Specification in a manner believed to be responsive to the requirement and without introducing any new matter therein. Applicant respectfully requests withdrawal of the objection.

**Claim Rejections -- 35 U.S.C. §102/§103**

Claims 1-8 and 21-33 are rejected under 35 U.S.C. §102(b) as being anticipated by United States Patent Number 6,032,342 to Kawabe et al. (Kawabe); and Claims 9-14 and 15-20 are rejected under 35 U.S.C. §103(a) as being unpatentable over Kawabe.

Applicant respectfully traverses the rejections for at least the following reason(s).

Claim 1 recites a carding machine for bundled fibers including a feed roll wound with the bundled fibers; a carding unit to card the bundled fibers drawn out from the feed roll with a fluid that flows in a direction that is orthogonal relative to a moving direction of the bundled fibers; and a rewind roll that rewinds a carded sheet formed by the bundled fibers that are carded in the carding unit, wherein the carding unit includes an internal frame that forms a fluid flow path, and a plurality of supporting parts placed along the moving direction of the bundled fibers between a front end and a back end in the moving direction of the bundled fibers within the frame.

Benefits derived from the structural arrangement of the features recited by Claim 1 are that: 1) a fiber height detection unit is not required as is the case in conventional carding machines; 2) a detection signal from such a fiber height detection unit is not needed to be feedback to a driver motor of a drive roll for a front feeder; 3) an upstream front feeder and drive motor can be omitted, thereby substantially reducing the number of parts needed for the machine; 4) a total length of an airflow carding action unit can be

reduced; 5) an overall weight of the carding machine is reduced; and 6) the overall manufacturing cost of the carding machine is reduced.

Kawabe does not disclose, teach or otherwise suggest a carding machine having the feature(s) recited by Claim 1.

For example, as shown in Figures 2, 11, 16, 21, and 23, while Kawabe discloses a suction cavity (4) having an aperture (41) that draws the multi-filament (F) therein so as to archly bend the multi-filament (F) due to velocity of the suction air blowing into the aperture (41), Kawabe does not disclose, teach or otherwise suggest a plurality of supporting parts that are laced along a moving direction of the bundled fibers between front and back ends in the moving direction of the fibers ***within an internal frame that forms a fluid flow path***. Rather, Kawabe teaches the suction cavity (4) is located below the moving multi-filament (F) such that the aperture (41) is open and receives a portion of the moving multi-filament (F) therein. A bending sensor (44) is provided in the suction cavity (4) to constantly measure a bending amount of the multi-filament (F) and sends a control signal corresponding to the measured value to a motor (33) of the front feeder (3) and controls the rotating speed of the roller to maintain a fixed bending amount of the multi-filament (F). See column 7, lines 19-23 and the paragraph bridging columns 7 and 8.

As is clear from the above, Kawabe teaches a conventional carding unit having the features, and deficiencies resulting therefrom, that is described in the beginning of Applicant's application. Accordingly, Kawabe suffers from at least the drawback of excessive feeding bundled fibers in the flow path having to (i.e., must) be bent or

formed into an arc shaped by the suction cavity (4) below, which is an indispensable element of the apparatus disclosed by Kawabe.

Moreover, Kawabe does not disclose, teach or otherwise suggest a carding unit that has the internal frame and plurality of supporting parts placed along the moving direction of the bundled fibers within the frame. Rather, Applicant respectfully submits that Kawabe expressly discloses the multi-filament (F) is maintained in a bent configuration while passing through the suction cavity, and therefore specifically teaches away from the invention recited by Claim 1. Further, Kawabe cannot provide the benefits provided by the claimed invention and suffers from the drawbacks and deficiencies of the conventional machines the present invention overcomes.

Put simply, Kawabe does not disclose, teach or otherwise suggest each and every feature recited by Claim 1.

To qualify as prior art under 35 U.S.C. §102, each and every feature recited in a rejected claim must be disclosed by the applied art. For at least the reasons provided above, Applicant submits that Kawabe does not disclose or suggest each and every feature recited by Claim 1. Accordingly, Kawabe does not anticipate, nor render obvious, the subject matter recited by Claim 1. Therefore, Applicant respectfully submits independent Claim 1 should be deemed allowable over Kawabe.

Claims 2-33 depend from Claim 1. It is respectfully submitted that these dependent claims be deemed allowable for the same reasons Claim 1 is allowable, as well as for the additional subject matter recited therein.

Applicant respectfully requests withdrawal of the rejections.


**Conclusion**

In view of the foregoing, Applicants respectfully request reconsideration of the application, withdrawal of the outstanding objections and rejections, allowance of Claims 1-33, and the prompt issuance of a Notice of Allowability.

Should the Examiner believe anything further is desirable in order to place this application in better condition for allowance, the Examiner is requested to contact the undersigned at the telephone number listed below.

In the event this paper is not considered to be timely filed, the Applicant respectfully petitions for an appropriate extension of time. Any fees for such an extension, together with any additional fees that may be due with respect to this paper, may be charged to counsel's Deposit Account No. 01-2300, **referencing attorney docket number 100725-00145.**

Respectfully submitted,

  
\_\_\_\_\_  
Murat Ozgu  
Registration No. 44,275

**Customer No. 004372**

**ARENT FOX LLP**

1050 Connecticut Avenue, N.W., Suite 400  
Washington, D.C. 20036-5339  
Tel: (202) 857-6000  
Fax: (202) 638-4810

MO:elp

Enclosures: Replacement Figs. 17-19(B)  
Clean Copy of Substitute Specification  
Marked-Up Copy of Substitute Specification

~~Description~~Carding Machine for Bundled Fibers

TECHNICAL FIELD

This~~[0001]~~ The invention relates to a machine that cards bundled fibers, wherein the bundled fibers ~~composed of many fiber filaments travel through a carding unit; into which fluid flows~~ orthogonally orthogonally relative to the moving direction of the bundled fibers ~~applying~~ and wherein a moving force is applied to the bundled fibers ~~so as to extend its, a~~ widthwise direction to card of the bundled fibers being extended so the bundled fibers can be carded into a sheet.

BACKGROUND ART

[0002] In recent years, many fiber-reinforced composite materials; have been developed in which a reinforcing material, such as carbon fibers, glass fibers, or aromatic polyamide fibers ~~as reinforcing material are impregnated in the form of a filament or fabric~~ form into a matrix, like a synthetic resin, ~~have been developed and are available on the market.~~

[0003] By correctly selecting both the matrix and reinforcing material, ~~these~~ the known fiber-reinforced materials have a wide-range of excellent properties that can be ~~matched to~~ utilized based on the desired objective of use with respect to mechanical strength, heat resistance, corrosion resistance, electric properties, and weight reduction ~~and~~. The known fiber-reinforced materials are widely used in the field of such technical fields as aerospace, land transportation, shipping, building, construction, industrial parts, and sporting goods.

[0004] There are two types of usage common uses of the reinforcing fibers. One common use is where the ~~structure~~ material is impregnated with the reinforcing filaments ~~into~~ to form a

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

matrix; while the other use is by parallel alignment of many filaments wide enough to cover the width of the matrix. In the latter ~~type~~use, it is desirable to make the contact area between the matrix and reinforcing filaments as large as possible. Therefore, many reinforcing filaments that are treated with an adhesive (sizing agent) are bundled ~~in a form of~~while having either a flat or ellipsoidal cross-section to form the bundled fibers, in which each reinforcing filament is aligned so as to minimize the space between them, ~~yielding~~wherein a thin but wide carded sheet is obtained. Impregnation of this the carded sheet in the matrix promotes the matrix to impregnate ~~into the minimum space, maximizing~~being impregnated into small spaces, wherein the contact area between the matrix and the reinforcing filament ~~and showing the maximum fiber is~~maximized, and the reinforcing filaments help maximize the reinforcing effects ~~by of~~ the reinforcing filaments. fibers.

For this purpose [0005] Accordingly, an airflow carding machine for the bundled fibers is proposed, disclosed in Japanese Patent Publication No. 3,064,019, wherein a so called suction wind tunnel pipe with a required ~~traverse~~predetermined width is placed ~~facing~~positioned to face a moving path ~~from~~of bundled fibers provided by a supply unit (feed roll) ~~of bundled fibers to a take-up section (rewind roll), and~~ wherein the bundled fibers (for example, multifilament) are continuously suctioned in a certain overfed condition ~~are continuously suctioned to bend the bundled fibers into a crescent shape and to card~~so the fibers can be carded in the widthwise direction ~~(Japanese Patent Publication No. 3,064,019).~~

[0006] The airflow carding machine for the bundled fibers disclosed in ~~this~~ Japanese Patent Publication No. 3,064,019 can effectively card ~~in parallel,~~ the bundled fibers of very long multifilaments in parallel without causing damage.

MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION

[0007] As shown in FIG. 17, the bundled fibers 1 are drawn out from a feed roll A that, and then ~~travels~~travel through a front feeder 2, which is ~~composed of~~includes a drive roll 2a and a free revolving roll 2b, into which an airflow carding unit 3 cards the fibers 1 to yield a carded sheet 1a. ~~This~~The carded sheet 1a is fed through a back feeder 4 to rewind the sheet 1a around a rewind roll B, and wherein the degree of bending of the bundled fiber 1 traveling through a suction wind tunnel 3a ~~in~~of the airflow carding unit 3 is detected by ~~the~~a fiber height detection unit 5 in the airflow carding machine for the bundled fibers 1. 5.

~~As shown in this figure, the fiber height detection unit 5 tries to use a method of controlling~~[0008] The fiber height detection unit 5 controls the level of bending of the bundled fibers 1, 1 by pressing down on all of ~~the whole~~ bundled fibers 1 with a wire-like fiber height sensor unit 5S, ~~detecting~~a, and then detects the location of a retaining unit 5b ~~that is tied~~ with ~~this~~the fiber height sensor unit 5a by a sensor 5c, which feeds back the detected signal to a driver motor of the driving roll 2a ~~in the front feeder 2. It adjusts the.~~ The number of revolutions and ~~controls~~ the amount of the bundled fibers 1 drawn out by the drive roll 2a and free revolving roll 2b, ~~adjusting for amount of overfeeding and controlling~~ is adjusted according to the amount of bundled fibers being overtaken as well as to control the amount of bending occurring to the bundled fibers.

DISCLOSURE OF INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0009] As shown in FIG. 18, more than one airflow carding unit 3.sub.1, 3.sub.2, 3<sub>1</sub>, 3<sub>2</sub>, and 3.sub.33<sub>3</sub> is aligned to form a multistage section in the moving direction of the bundled fibers since a single airflow carding unit 3 alone cannot sufficiently card the bundled fibers ~~collected~~



with many filaments. In this case, as shown in FIG. 18, feed roll units ~~2.sub.1, 2.sub.2,~~  
~~2.sub.3, 2<sub>1</sub>, 2<sub>2</sub>, 2<sub>3</sub>,~~ and 4 are installed before and after each airflow carding unit ~~3.sub.1,~~  
~~3.sub.2, 3<sub>1</sub>, 3<sub>2</sub>,~~ and ~~3.sub.3 3<sub>3</sub>~~ together with the aforementioned fiber height detection units  
~~5.sub.1, 5.sub.2, 5<sub>1</sub>, 5<sub>2</sub>,~~ and ~~5.sub.3 5<sub>3</sub>~~ at each airflow carding unit ~~3.sub.1, 3.sub.2, 3<sub>1</sub>, 3<sub>2</sub>,~~ and  
~~3.sub.3, 3<sub>3</sub>,~~ respectively, in order to make the carding process proceed smoothly at each airflow  
carding unit ~~3.sub.1, 3.sub.2, and 3.sub.3. 3<sub>1</sub>, 3<sub>2</sub>, and 3<sub>3</sub>,~~

### SUMMARY OF THE INVENTION

The main objective [0010] An aspect of the present invention is to provide a carding machine  
capable of continuously carding the bundled fibers without ~~detecting~~ having to detect the level  
of bending of the bundled fibers in the carding unit by using the fiber height detection unit that  
feedbacks its ~~a~~ detected signal to the driver motor ~~for of~~ the ~~drive roll of the front feeder~~ drive  
roll to control the depth of bending as is done in the aforementioned conventional airflow  
carding machine.

[0011] Another ~~purpose~~ aspect of the present invention is to provide a compact, lightweight,  
and economical carding machine ~~for the bundled fibers~~, wherein ~~more~~ uniform and highly carded  
filaments ~~can be~~ are constantly produced by ~~use of~~ fusing one or more supportive parts with a  
small diameter in the carding unit.

[0012] An additional ~~objective~~ aspect of the present invention is to simplify the support  
structure of the feed roll such that the required space for installation is reduced and ~~obtain a~~  
carding machine with multiple ~~spindles~~ spindles or multiple spindle multistage bundled fibers is  
obtained.

### MEANS FOR SOLVING PROBLEM

[0013] In order to achieve the aforementioned ~~objective~~ aspects, the carding machine for  
bundled fibers in the present invention is ~~first characterized by having the~~ includes a carding unit

to card ~~card~~which cards the bundled fibers ~~that are~~ fed from a feed roll wound with the bundled fibers; by flowing fluid in a direction that is orthogonal relative to the moving direction of the ~~moving~~ bundled fibers; by having a rewind roll rewinding the carded sheet in the carding unit; and by having one or more supportive parts placed in a ~~certain~~predetermined interval along the moving direction ~~in the aforementioned carding unit~~.

In this setup [0014] According to the above-described structural configuration, the direction that the fluid flows in the carding unit can either suction the fluid flowing downward, from above to below, or flowing upward, from below to above, so long as the fluid flows in the direction that is orthogonal relative to the moving direction of the bundled fibers. Similarly, ~~this relationship holds in the case where the~~the suction fluid flow direction can be such regardless as to whether the fluid flow direction is ~~from right to left or from left to right~~.

[0015] Increasing the number of supportive parts in the ~~said~~ carding unit reduces the interval distance, as well as the bending of the bundled fibers, between the supportive parts, whereas increasing ~~their~~the diameter of the supportive parts increases the ~~modulus~~number of supportive parts to prevent bending and reducing their interval distance, leading to a decrease of bending of the bundled fibers between the supportive parts. However, increasing the number of supportive parts or the diameter thereof tends to excessively reduce the flow area of the fluid, along with ~~reducing~~ the interval distance, resulting in a decrease in the carding efficiency of the fluid. Therefore, the number, diameter, and interval distance of ~~said~~the supportive parts ~~need~~needs to be properly set according to the kind of bundled fibers, the diameter and number of the filaments, and the kind of a sizing agent.

[0016] The aforementioned one or more supportive parts that are installed at a particular interval ~~are properly placed~~can be positioned linearly ~~and~~, horizontally, tilted, or in a crescent shape, according to the type of bundled fibers, the diameter and number of the reinforcing filament, and the kind of sizing agent. ~~(Refer to FIG. 4 (A), FIG. 6 (B), and FIG. 8.)~~

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

~~In the carding machine for the bundled fibers in the present invention, the said carding unit is secondly characterized by having a frame forming a flow path for the fluid internally and possessing both a large diameter guiding part placed at the front and back ends of the guiding part in the moving direction of the bundled fibers and one or more small diameter supportive parts placed between these guiding parts.~~

~~The carding machine for the bundled fibers in the present invention is thirdly characterized by a guiding and/or supportive part in the aforementioned carding unit having a roughly cylindrical form and a fixed or revolvable form around a shaft.~~

~~The carding machine for the bundled fibers in the present invention is fourthly characterized by placing the aforementioned multiple supportive parts in a plane or roughly, in a crescent, against the moving direction of the bundled fibers.~~

~~The carding machine for the bundled fibers in the present invention is fifthly characterized by placing the aforementioned carding unit in multistage along the moving direction of the bundled fibers.~~

~~The carding machine for the bundled fibers in the present invention is sixthly characterized by increasing stepwise or continuously the width of the moving path of the bundled fibers in the aforementioned multistage carding unit with the direction going from upstream to downstream.~~

~~The carding machine for the bundled fibers in the present invention is seventhly characterized by placing the shaft of the aforementioned feed roll in a vertical direction. Here, "vertical direction" includes not only a geometrically perpendicular arrangement, but also a tilted arrangement at a certain angle relative to the perpendicular.~~

~~The carding machine for the bundled fibers in the present invention is eighthly characterized by placing more than one aforementioned feed rolls.~~

MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION

~~The carding machine for the bundled fibers in the present invention is ninthly characterized by placing more than one carding unit in parallel and orthogonal to the moving direction of the bundled fibers.~~

~~The carding machine for the bundled fibers in the present invention is tenthly characterized by consolidating the carding unit into a single carding form that shares a part of the component part, wherein the carding unit is placed in multistage along the moving direction of the aforementioned bundled fibers, and/or more than one carding unit is placed in parallel and orthogonal to the moving direction of the bundled fibers.~~

~~An eleventh characterization of the carding machine for the bundled fibers in the present invention is a fluid path filled with a heated fluid.~~

~~A twelfth characterization of the carding machine for the bundled fibers in the present invention is heating of the guiding and/or supportive parts in the aforementioned carding unit.~~

~~A thirteenth characterization of the carding machine for the bundled fibers in the present invention is having the aforementioned guiding and/or supportive parts with a built-in heater.~~

~~A fourteenth characterization of the carding machine for the bundled fibers in the present invention is having the aforementioned guiding and/or supportive parts in a pipe shape, in which heated fluid is circulated.~~

~~A fifteenth characterization of the carding machine for the bundled fibers in the present invention is having a slit in the aforementioned pipe shaped guiding and/or supportive parts that crosses in the moving direction of the bundled fibers, wherein the heated fluid is ejected from this slit.~~

#### ADVANTAGEOUS EFFECT OF THE INVENTION

[0017] According to the first characteristic of the aforementioned structure of the carding machine for the bundled fibers in the present invention, the carding unit possesses one or more supportive parts arranged orthogonal relative to the moving direction of the bundled fibers and

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

the carding action in the conventional wind tunnel pipe performed by passing the bundled fibers and the carded sheet over one or more supportive parts aligned at small intervals is done before and after on both sides of the single supportive part, or continuously done before and after in small stepwise intervals for each of the more than one supportive parts, leading to more reliable carding action and better quality in carding.

[0018] Furthermore, the bundled fibers moving in the carding unit ~~is~~are constantly carded, responding to the alignment condition of one or more supportive parts. Therefore, ~~it is not~~the **fiber height detection unit** required to ~~use~~by the conventional method, in which the height of the moving bundled fibers is balanced by an airflow suction force with the tension of the bundled fibers to bend into a crescent form that is constantly detected by the fiber height detection unit and fed back to the driver motor of the drive roll of the front feeder to control for the amount of overfeeding of the bundled fibers fed from the front feeder. Omitting the fiber height detection unit between carding units in each step, as well as the front feeder, particularly in a multistage carding machine, **machines is omitted, which** leads to a smaller, lightweight, cheaperand less costly carding machine.

As it relates to the setup of the second characteristic of [0019] **In** the carding machine for the bundled fibers ~~in~~of the present invention, **the carding unit also includes** a frame forming a flow path for the fluid **and possesses both** a large diameter guiding part is placed at the front and at the end of the frame ~~back ends of the guiding part~~ in the moving direction of the bundled fibers and one or more small diameter supportive parts placed between these guiding parts.

[0020] **According to the aforementioned structure of the carding machine,** and the bundled fibers are stably fed into the carding unit that ~~and~~and stably comes ~~pass~~pass out from the carding unit. Furthermore, one or more small diameter supportive parts are installed between these guiding

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

parts, and the bundled fibers moving in the carding unit can be kept ~~at~~in a constant configuration that ~~responds~~corresponds to the placement of the single or multiple supportive parts, leading to uniform carding and ~~then an elimination of~~eliminates the requirement of detecting the fiber height in the carding unit. ~~Using~~That is, using smaller diameter supportive part makes the fluid flow path area larger to improve, thereby improving carding action in the carding unit.

~~In regards to the structure of the third characteristic of the~~[0021] ~~The~~ carding machine for the bundled fibers ~~in~~of the present invention, ~~the~~also includes a guiding and/or supporting parts ~~are~~supportive part that has a roughly cylindrical ~~and are either~~form and a fixed or revolvable ~~form around the shaft, where the~~shaft.

[0022] According to the aforementioned structure of the carding machine, a friction force generated by the flow force of the fluid from the guiding and/or supporting parts ~~apply~~applies a smooth carding action to the moving bundled fibers over the guiding and/or supportive parts. When the guiding and/or supportive parts are fixed, their structure becomes simple and the machine can be manufactured at low cost. When the guiding and/or supportive parts are able to revolve around the shaft, ~~they~~the guiding and/or supportive parts revolve around the shaft by moving bundled fibers ~~as to make its movement~~ of the bundled fibers smooth and reduce the friction between the bundled fibers and the guiding and/or supportive parts. Furthermore, the area of friction ~~can be~~is diffused in a circumferential direction to prolong the life of the guiding and/or supportive parts.

~~According to the setup of the fourth characteristic of the~~[0023] ~~The~~ carding machine for the bundled fibers ~~in~~of the present invention, ~~more than one~~further includes multiple supportive part ~~is placed~~parts positioned in a plane or ~~approximately~~roughly, in a crescent ~~shape~~, against the moving direction of the bundled fibers, ~~and~~.

[0024] According to the aforementioned structure of the carding machine, the bundled fibers moving on the supportive parts can move and can be carded constantly, keeping a planar or crescent configuration against the moving direction according to the setup of the supportive parts, thereby making efficient carding possible. In the case that the bundled fibers are carded in the crescent configuration, an excess mass of the overfed bundled fibers can be absorbed by sinking of the fibers, so that the contact area between the bundled fibers and fluid is increased, improving wherein the carding efficiency is improved, especially when compared to the case where multiple supportive parts are set flat.

~~According to the setup of fifth characteristic of the~~[0025] The carding machine for the bundled fibers ~~in of~~ the present invention also includes placing the carding unit in a multistage format along the moving direction of the bundled fibers.

[0026] According to the aforementioned structure of the carding machine, the carding unit is aligned in multiple stages along the moving direction of the bundled fibers, and carding of the bundled fibers is processed step by step and, smoothly moving along the bundled fibers over the multistage carding unit from an upstream end to a downstream end. In this case, ~~not only the fiber height detection unit at each carding unit, but also the front feeder upstream of each carding unit is~~ also not required, so as to simplify, miniaturize, lighten, and minimize cost and shorten which simplifies, miniaturizes, lightens, and minimizes cost and shortens the total length of the carding machine.

~~In regards to the sixth characteristic of the~~[0027] The carding machine for the bundled fibers ~~in of~~ the present invention may further include increasing stepwise, or continuously, the width of the moving path of the bundled fibers.

[0028] According to the aforementioned structure of the carding machine, the width of the flow path for the bundled fibers in the multistage carding unit ~~becomes~~is more orderly, stepwise or continuously, from the upstream end to the downstream end, and carding of the bundled fibers is progressed to adjust for this widening, as the bundled fibers move from the upstream ~~to~~end to the downstream end, to pass the carding unit in each stage, smoothly yielding a carded sheet.

[0029] The carding machine of the present invention further places the shaft of the feed roll in a vertical direction. Here, "vertical direction" includes not only a geometrically perpendicular arrangement, but also a tilted arrangement at a certain angle relative to the perpendicular.

~~In regards~~[0030] According to the seventh characteristicaforementioned structure of the carding machine ~~for the bundled fibers in the present invention, the feed roll is placed vertically to the shaft and,~~ the supply position of the bundled fibers relative to the guide roll at the entrance of the carding action section sways ~~little when~~less compared to the conventional machine, which ~~has~~arranges the shaft of the feed roll horizontally. Furthermore, the degree of swaying of the bundled fibers is absorbed along the circumference of the guide roll so that the feed roll is not required to traverse the shaft direction, ~~and the structure of the supporting action section can be simplified,~~ and the required space for ~~the~~ installation of the feed roll ~~can be~~is reduced.

~~As it relates to the structure of eighth characteristic of the~~[0031] The carding machine for the bundled fibers ~~in~~of the present invention, ~~more than one of the said feed rolls is installed~~ includes a plurality of feed rolls.

[0032] According to the aforementioned structure of the carding machine, more than one set of bundled fibers ~~are~~can be fed from each feed roll so as to be carded at the carding unit ~~to~~



yield, thereby yielding a wide carded sheet. Furthermore, as each shaft of multiple feed rolls is positioned vertically, more than one feed roll can be placed close to each other to achieve a multiple spindle carding machine, which was difficult to obtain previously.

~~In regards to the setup of the ninth characteristic of the~~[0033] The carding machine for the bundled fibers in the present invention, more than one carding unit is aligned in parallel~~of the present invention includes a plurality of carding units positioned in parallel and orthogonal relative to the moving direction of the bundled fibers.~~

[0034] According to the aforementioned structure of the carding machine, aligning a plurality of carding units in parallel, but orthogonal relative to the moving direction of the bundled fibers, ~~and more than one set of bundled fibers from the multiple feed rolls can travel over more than one carding unit that is aligned in parallel,~~ to simultaneously card so as to give a multiple spindle sequential carding machine that ~~can produce~~produces a wider carded sheet, which was previously difficult to obtain.

[0035] The carding machine of the present invention consolidates the carding unit into a single carding form that shares a part of the component part, wherein the carding unit is placed in a multistage format along the moving direction of the aforementioned bundled fibers, and/or more than one carding unit is positioned in parallel but orthogonal relative to the moving direction of the bundled fibers.

~~Relating~~[0036] According to the aforementioned structure of the ~~tenth characteristic of the carding machine for the bundled fibers in the present invention,~~ the multistage carding unit is placed in the moving direction of the bundled fibers, and/or more than one carding unit is placed~~placed~~positioned in parallel but orthogonal relative to the moving direction of the bundled fibers to consolidate into a sequentially integrated form, sharing at least a part of the component

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

materials for the fluid flow path, spacer, and guiding part. ~~Not~~As such, not only is a wide carded sheet ~~smoothly~~ obtained, but also the number of component parts is reduced to save on material costs when compared to the alignment of more than one carding unit in series or in parallel ~~in multistage~~. Furthermore, the length and/or width in the sequentially integrated carding unit can ~~be~~is reduced to achieve miniaturization, weight reduction, and cost saving of the carding machine.

~~According to the eleventh characteristic of the~~[0037] ~~The~~ carding machine for the bundled fibers ~~in~~of the present invention includes a fluid path filled with a heated fluid.

[0038] According to the aforementioned structure of the carding machine, a sizing agent sticking to the bundled fibers is heated to melt in the carding unit that is heated by a fluid to weaken the bonding force between the reinforced fibers forming the bundled fibers, thereby improving the carding efficiency of the bundled fibers.

~~In regards to the twelfth characteristic of the~~[0039] ~~The~~ carding machine for the bundled fibers ~~in~~of the present invention, ~~the bundled fibers are heated by~~ includes heating the guiding and/or supportive parts in the carding unit, and the sizing agent sticking to the bundled fibers is heated to melt and weaken the bonding force between the reinforced fibers forming the bundled fibers to improve the carding efficiency of the bundled fibers.

Relating to the thirteenth characteristic  
[0040] According to the aforementioned structure of the carding machine for the bundled fibers in the present invention, ~~the bundled fibers are heated by the guiding parts and/or supportive parts with a built-in heater, and the sizing agent sticking to the bundled fibers is heated to melt and weaken the bonding force between the reinforced fibers forming the bundled fibers,~~ the bundled fibers are heated by heating the guiding and/or supportive parts in the

carding unit, and the sizing agent sticking to the bundled fibers is heated to melt and weaken the bonding force between the reinforced fibers forming the bundled fibers, thereby improving the carding efficiency of the bundled fibers.

[0041] The carding machine of the present invention includes providing the guiding and/or supportive parts with a built-in heater.

[0042] According to the aforementioned structure of the carding machine, the bundled fibers are heated by the guiding parts and/or supportive parts with a built-in heater, and the sizing agent sticking to the bundled fibers is heated to melt and weaken the bonding force between the reinforced fibers forming the bundled fibers, thereby improving the carding efficiency of the bundled fibers.

[0043] The carding machine of the present invention includes having the aforementioned guiding and/or supportive parts in a pipe shape, in which heated fluid is circulated.

In relation ~~to the fourteenth characteristic~~ [0044] According to the ~~fourteenth characteristic~~ aforementioned structure of the carding machine ~~for the bundled fibers in the present invention,~~ the bundled fibers are heated by the guiding and/or supportive parts which in turn has been heated by a heated fluid, and the sizing agent sticking to the reinforced fibers forming the bundled fibers is heated, melting and weakening the bonding force ~~to improve,~~ thereby improving the carding efficiency of the bundled fibers.

[0045] The carding machine of the present invention includes a slit in the aforementioned pipe shaped guiding and/or supportive parts that crosses in the moving direction of the bundled fibers, wherein the heated fluid is ejected from the slit.

In regards ~~to the fifteenth characteristic~~ [0046] According to the ~~fifteenth characteristic~~ aforementioned structure of the carding machine ~~for the bundled fibers in this invention,~~ the bundled fibers are heated by the

heated fluid ejected from the slits of the pipe shaped guiding parts and/or supportive parts, and the sizing agent sticking to the bundled fibers is heated, melting and weakening the bonding force between the reinforced fibers forming the bundled fibers, and—drastically ~~improve~~improving the carding efficiency of the bundled fibers via the carding action of the heated fluid.

#### BRIEF DESCRIPTION OF DRAWINGS

[0047] FIG. 1 is a front view of the airflow carding machine for a single spindle bundled fiber according to ~~the~~a first embodiment ~~in~~of the present invention~~;~~;

[0048] FIG. 2 is a schematic ~~planar view~~diagram of the supply unit for the bundled fibers ~~aeecording to~~of the machine shown in FIG. 1~~;~~;

[0049] FIG. 3 is an enlarged planar view of the multistage airflow carding unit according to the machine shown in FIG. 1~~;~~;

[0050] FIG. 4 (A) is a front sectional view of the first stage airflow carding unit ~~aeecording to~~of the multistage airflow carding unit shown in FIG. 3~~;~~;

[0051] FIG. 4 (B) is a side view of the first stage airflow carding unit ~~aeecording to~~of the multistage airflow carding unit shown in FIG. 3~~;~~;

[0052] FIG. 4 (C) is a side view of the second stage airflow carding unit ~~aeecording to~~of the multistage airflow carding unit shown in FIG. 3~~;~~;

[0053] FIG. 4 (D) is a side view of the third stage airflow carding unit ~~aeecording to the multistage airflow carding unit in FIG. 3.~~of the multistage airflow carding unit shown in FIG. 3;

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

[0054] FIG. 5 (A) is a schematic ~~planar view~~diagram of the components in ~~the~~an airflow carding machine for multiple spindle bundled fibers according to ~~the~~a second embodiment ~~in of~~ the present invention-;

[0055] FIG. 5 (B) is a schematic ~~frontal view~~diagram of the components for the machine shown in FIG. 5 (A)-;

[0056] FIG. 6 (A) is a ~~partly~~an enlarged planar view of ~~the~~a sequentially integrated airflow carding unit in the airflow carding machine ~~for the multiple spindle bundled fibers~~shown in FIG. 5-5;

[0057] FIG. 6 (B) is an enlarged frontal view of the sequentially integrated airflow carding unit shown in FIG. 6 (A)-;

[0058] FIG. 6 (C) is an enlarged frontal view of ~~the~~ key components shown in FIG. 6 (B)-;

[0059] FIG. 7 is a schematic ~~frontal view~~diagram of ~~the~~a multistage airflow carding machine for ~~the~~a double decked form of the multiple spindle bundled fibers ~~in the~~according to a third embodiment of the present invention-;

[0060] FIG. 8 is a front sectional view of ~~the~~an airflow carding unit according to ~~the~~a fourth embodiment of the present invention-;

[0061] FIG. 9 is a schematic ~~frontal view~~diagram of ~~the~~an airflow carding machine according to ~~the~~a fifth embodiment of the present invention, wherein the airflow carding unit shown in FIG. 8 is used-;

[0062] FIG. 10 is a schematic ~~frontal view~~diagram of ~~the~~a front feeder in the airflow carding machine shown in FIG. 9-9;

[0063] FIG. 11 is a schematic ~~enlarged frontal view~~diagram of ~~the~~a fiber height detection unit in the airflow carding machine shown in FIG. 9-9;

MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION

[0064] FIG. 12 (A) is a schematic ~~planar view~~diagram of ~~the~~a carding machine for the multiple spindle bundled fibers according to ~~the~~a sixth embodiment of the present invention-;

[0065] FIG. 12 (B) is a schematic ~~frontal view~~diagram of ~~the~~a carding machine for the multiple spindle bundled fibers shown in FIG. 12 (A)-;

[0066] FIG. 13 (A) is ~~an enlarged~~a side view of an upstream feed roll in a stationary state of the bundled fibers in the airflow carding machine for the multiple spindle bundled fibers shown in FIG. ~~12-~~12;

[0067] FIG. 13 (B) is an enlarged frontal view of the feed roll shown in FIG. 13 (A)-;

[0068] FIG. 13 (C) is an enlarged ~~frontal view~~diagram of the feed roll, in the fed state, shown in FIG. 13 (A)-;

[0069] FIG. 14 is a schematic ~~frontal view~~diagram of ~~the~~a carding machine for ~~the~~a double decked form of the multistage multiple spindle bundled fibers according to ~~the~~a seventh embodiment of the present invention-;

[0070] FIG. 15 (A) is an exploded perspective view of ~~the key parts, showing the~~a support structure of ~~the~~a supportive part in ~~a different embodiment in the~~of a carding machine for the multiple spindle bundled fibers in accordance to an eighth embodiment of the present invention-;

[0071] FIG. 15 (B) is a vertical sectional view of the support structure of the supportive parts in the carding machine for the multiple spindle bundled fibers shown in FIG. 15 (A)-;

[0072] FIG. 16 (A) is a schematic ~~sectional view in the~~embodimentdiagram of the airflow carding unit ~~comprised of~~having heated gas-;

[0073] FIG. 16 (B) is an enlarged sectional view of ~~the embodiment of the~~a pipe shaped guiding and/or supportive parts equipped with a built-in heater-;

MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION

[0074] FIG. 16 (C) is an enlarged sectional view ~~of the embodiment~~, wherein the guiding and/or supportive parts are pipe-shaped and ~~circulated with~~ circulate heated fluid through the inside of hollow pipe.;

[0075] FIG. 16 (D) is an enlarged sectional view ~~illustrating~~ wherein the guiding and/or supportive parts have ~~the~~ a pipe shape and slits that cross the carded sheet, and wherein heated gas is circulated inside the hollow pipe.;

[0076] FIG. 17 is a schematic frontal view ~~in~~ of a conventional airflow carding machine ~~for the bundled fibers.~~;

[0077] FIG. 18 is a schematic frontal view of a conventional airflow carding machine for the multistage bundled fibers.;

[0078] FIG. 19 (A) is a schematic frontal view ~~of the feed unit of the bundled fibers that illustrates one of~~ diagram illustrating one of the problems in the conventional machine shown in FIG. 18. 18; and

[0079] FIG. 19 (B) is a schematic planar view of the feed unit ~~of the bundled fibers~~ shown in FIG. 19 (A).

~~BEST MODE FOR CARRYING OUT~~ DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

[0080] Various embodiments according to the present invention are described below with reference to the accompanying drawings.

FIRST EMBODIMENT

[0081] FIG. 1 shows a frontal view of the airflow carding machine for a single spindled bundled fiber according to ~~the~~ a first embodiment ~~in~~ of the present invention. In FIG. 1, a unit 10 is the bundled fiber feeding unit (filament feeding unit). As shown in the planar view of the key parts in FIG. 2, a feed roll 13, around which bundled fibers 12 composed of a large number of reinforced filaments, such as carbon fibers, bonded by a sizing agent are wound, is supported on a table 11 positioning ~~its~~ a shaft ~~in~~ of the feed roll 13 in a vertical direction and freely revolving~~ing~~rotating around it. ~~Part 14 is at~~ the shaft. A guide roll, 14, which changes the moving direction of the bundled fibers 12 ~~that are fed from the feed roll 13, by approximately 90 degrees in a planar view, and its~~ a shaft of the guide roll 14 is fixed vertically ~~or~~ for the guide roll 14 to freely revolving~~ing~~rotate around the shaft. ~~Part~~ A guide roll 15 is ~~a guide roll which sends the bundled fibers 12, 12 that are sent from at~~ the guide roll ~~14, 14 to an airflow carding action unit 20 at a certain height and, is fixed or freely revolving~~ 14, 14 to an airflow carding action unit 20 at a certain height and, is fixed or freely revolvingrotating, as ~~later~~ will be described later.

Said [0082] The feed roll 13 is equipped with an adjustable tension applying means 16, which applies tension to the bundled fibers 12, optimizing the tension applied to the bundled fibers 12 according to the properties and size of the reinforced filaments to form the bundled fibers 12 and the kind of the sizing agents used.

Unit 20 is an [0083] An airflow carding action unit, ~~which is composed of more than one~~ 20 includes a plurality of guide roll, rolls 21 and 22, a multistage airflow carding unit 25 that has more than one airflow carding unit (in the example drawing, three units of airflow carding units 25a, 25b, and 25c) aligned in series in the moving direction of the bundled fibers 12, and a rewind roll unit 28 ~~to rewind~~ that rewinds the carded sheet 12a. ~~It, which~~ which is then carded in the multistage airflow carding unit 25.



MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION

[0084] As shown in FIG. 3 and FIGS. 4 (A) to 4 (D), the multistage carding action unit 25 is composed of includes a multistage alignment of ~~three~~ airflow carding units 25a, 25b, and 25c, in series, from an upstream end to a downstream end. As shown in FIG. 3 and FIGS. 4 (A) to 4 (D), a width of a moving path w1, w2, and w3, ~~3~~ for the bundled fibers 12 in each airflow carding unit 25a, 25b, and 25c becomes broader as ~~it~~ the path moves downstream in the moving direction of the bundled fibers ( $w1 < w2 < w3$ ). Except for ~~the~~ width, as will be described later, each airflow carding unit 25a, 25b, and 25c has a very similar structure.

[0085] Therefore, the exemplary airflow carding unit 25a will be ~~used to illustrate our~~ example. ~~Airflow~~ referenced herein to describe aspects of the invention. For example, the airflow carding unit 25a has an airflow wind tunnel, such as a hollow rectangular wind tunnel 250 250, that forms a suction wind tunnel ~~sucked~~ that suctions air from ~~the~~ a lower side. It is The airflow carding unit 25a also ~~equipped with~~ includes large diameter guiding parts 252 and 253, which extend to sideboards 251 on both ends and are placed before and after the moving direction of the bundled fibers 12. ~~They~~ The sideboards 251 are horizontal and orthogonal relative to the moving direction of the bundled fibers 12 ~~and horizontal~~. 12. The airflow carding unit is 25a also ~~equipped with~~ includes more than one small diameter supportive part 254 placed at a certain interval between the guiding parts 252 and 253, in the same plane and horizontally relative thereto.

[0086] Guiding parts 252 and 253 and/or supportive part 254 can be fixed on sideboards 251 and 251 of the wind tunnel 250, or can be free to revolve around ~~its~~ a shaft. If the guiding parts 252 and 253 and/or supportive part 254 are fixed to sideboards 251 and 251, the support structure is simplified, thereby cutting production cost. If the guiding parts 252 and 253 and/or supportive part 254 are ~~freeable~~ to revolve freely rotate, as is sometimes desirable, depending on

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

the property and size of the reinforced filament forming bundled fibers 12 and the kind of sizing agent, the moving and carding of bundled fibers 12 become smoother, reducing wear by friction with the bundled fibers 12 and preventing uneven wearing by constantly changing the friction location relative to the circumference direction.

[0087] Inside of each of ~~sideboards~~ sideboard 251 and 251, the guiding parts 256 and 256 ~~regulates~~ regulate the crosswise movement of the bundled fibers 12 and are placed positioned by flexible spacer parts 255a, 255b, and 255c that are slightly higher than the guiding parts 252 and 253 to control the vertical positioning of the bundled fibers 12. Increasing the height of the said guiding parts 256 and 256 ~~makes~~ provides the airflow in the airflow carding unit with a stable laminar flow and stabilizes the carding action of the bundled fibers 12. However, increasing the height beyond a certain level does not give higher result in greater stabilization of the carding action by the stabilization of airflow. Rather ~~it,~~ increasing the height too much gives rise to a larger size and higher cost of the machine. Therefore, the height of the guiding parts 256 and 256 is to be ~~properly~~ determined according to the properties and size of the reinforced filament in the bundled fibers 12 and the kind of the sizing agent used.

~~Sideboards~~ [0088] The sideboards 251 and 251 ~~that are on both sides,~~ 251, spacer parts 255a, 255b, and 255c, and guiding parts 256 and 256 in the aforementioned airflow carding units 25a, 25b, and 25c are ~~tied together with~~ connected by bolts 257 and 257 ~~while being able~~ so as to be easily disassembled. ~~Screw~~ A screw hole ~~258~~ 258, so as to fix the guiding parts, is drilled into sideboards 251 and 251 in each airflow carding units 25a, 25b, and 25c, such as to match the end of the moving direction of the bundled fibers.

[0089] Thickness t1, t2, and t3 of each spacer 255a, 255b, and 255c in the airflow carding units 25a, 25b, and 25c, are placed along the moving direction of the bundled fibers 12 in descending

order  $t_1 > t_2 > t_3$ . Namely, the thickness decreases in the moving downstream, such as where the width of moving path,  $w_1$ ,  $w_2$ , and  $w_3$  for bundled fibers 12 formed between the guiding parts 256 and ~~256~~256, are in the order of  $w_1 < w_2 < w_3$ , where the width increases as it moves moving in the downstream direction. This configuration makes the width of the carded sheet 12a adjustable with the progress of the carding of the bundled fibers 12. Spacers 255a, 255b, and 255c, and guiding parts 256 and ~~256~~256, are consolidated by bolts 257 and 257 ~~for~~to the sideboards 251 and 251 in order to allow for the sharing of components, except for the spacers, in the airflow carding units 25a, 25b, and 25c, giving added flexibility in the assembly and disassembly of the parts by exchanging the spacers 255a, 255b, and 255c with different thicknesses,  $t_1$ ,  $t_2$ , and  $t_3$ .

[0090] The carding action in the aforementioned airflow carding machine for the single spindled bundled fibers is described next. The bundled fibers 12 are drawn out from the feed roll 13 to change the moving direction by approximately 90 degrees within a horizontal plane by a guide roll 14 and is kept at a certain height by a guide roll 15 to draw out to the airflow carding action unit 20.

[0091] The bundled fibers 12 traveling through the guide rolls 21 and 22 that have a tape shaped or elliptical cross-section are drawn out in the moving direction to be carded at the airflow carding unit 25, forming the carded sheet 12a. ~~This~~The sheet 12a is composed of crosswise lining of each reinforced filaments, which are then rewound around a rewinding roll unit 28.

[0092] As bundled fibers 12 are drawn out from the feed roll 13, which is stacked in a vertical direction, the drawn out height of the bundled fibers 12 can be moved up and down. However, the bundled fibers 12 that are drawn out change ~~its~~their direction by approximately 90 degrees in

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

planar view by a guide roll 14 that is stacked vertically, and are pressed from above and below by a guide roll 15 that is placed horizontally. Therefore, the bundled fibers 12 only pitch slightly at the entrance of guide roll 15. Furthermore, since the shaft of guide roll 15 is placed horizontally, the bundled fibers 12 are guided along the circumference of the guide roll 15. When compared to the conventional machine, in which the shaft of both the feed roll A and the guide roll 2 is placed horizontally, as shown in FIGS. 19 (A) and 19 (B), swaying of the feed position for the bundled fibers 12 that are fed through guide roll 15 is extremely low. This leads to stabilization of the supply position in the bundled fibers 12 towards the airflow carding action unit 20. As in the conventional machine, the feed roll is not required to traverse towards the shaft direction and the required space for the installation of feed roll 13 ~~can be~~ is reduced.

[0093] ~~Since a proper level of load~~ level is applied to the feed roll 13 by the tension applying means 16, a proper level of tension is applied to the bundled fibers 12 drawn out from the feed roll 13. Both the tension by the tension applying means 16 at the feed roll 13 and the rewinding tension by the rewind roll unit 28 constantly apply proper tension to ~~both~~ the bundled fibers 12 and the carded sheet 12a.

[0094] ~~Since each airflow carding unit~~ unit 25a, 25b, and 25c in the multistage airflow carding unit 25 ~~are~~ is equipped with guiding parts 252 and ~~253~~ 253, and more than one supportive part 254 that ~~are~~ is placed ~~in a plane and horizontally~~ in a plane, a downward airflow in the suction wind tunnel keeps the bundled fibers 12 in contact with the planar and horizontal supporting part 254 so as to constantly maintain ~~them~~ the bundled fibers 12 in a horizontal plane ~~and horizontally~~. Therefore, as shown in FIG. 17, the fiber height detection units 51, 52, and 53 are not required ~~to install in each of~~ the airflow carding units 25a, 25b, and 25c. Therefore, as in the conventional case, ~~its~~ a detection signal is not required to feedback to the driver motor of the

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

drive roll for front feeders 21, 22, and 23. The upstream front feeder and driver motor in each airflow carding unit 25a, 25b, and 25c can be omitted to drastically reduce the number of machine parts, shortening the total length of airflow carding action unit 20, and possibly achieving miniaturization, weight reduction, and lowering the cost of the whole-airflow carding machine.

[0095] As described above, the fiber height of the bundled fibers 12 and carded sheet 12a are kept in a horizontal plane and horizontally by guide parts 252 and ~~253~~253, and more than one supporting parts ~~254~~part 254, in each airflow carding unit 25a, 25b, and 25c. Further, ~~they~~the bundled fibers 12 are smoothly carded in the airflow carding units 25a, 25b, and 25c by adjusting the tension applying means 16 of the feed roll 13 and the number of revolutions of the driver motor for the rewind roll unit 28. Adjusting the tension to a constant level in rewinding of the carded sheet 12a to the rewind roll unit 28 eliminates pitching of the rewound carded sheet 12a to yield a roll of high quality carded sheet 12a.

[0096] According to the carding machine for the single spindle multistage bundled fibers described above, the carding action, ~~in which~~wherein the bundled fibers 12 or carded sheet 12a ~~travel~~travel over each airflow carding unit 25a, 25b, and 25c, and ~~passes~~pass over more than one supportive parts 254, is performed at small intervals, stepwise, and continuously when compared to the carding action by a conventional wind tunnel, leading to more reliable carding and an improvement in the quality of the carded product.

[0097] Since the bundled fibers 12 or carded sheet 12a travels over each airflow carding unit 25a, 25b, and 25c and is kept horizontal by more than one supportive part 254, it is not required to install a fiber height detection unit, in which a front feeder is installed upstream of each airflow carding unit, 25a, 25b, and 25c to detect the fiber height of the bundled fibers 12 or

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

carded sheet 12a that travels over each airflow carding unit, 25a, 25b, and 25c and feedbacks the detected signal to a driver motor of the upstream front feeder. Along with the elimination in the need of the front feeder and its driver unit, it is also not necessary to have a processing and controlling unit for the detected signal. This not only simplifies its structure and reduces cost, but also eliminates the required space for installation, reducing its size, weight, and cost of the whole airflow carding machine for the bundled fibers. ~~These~~**The beneficial** effects become more obvious as the number of stage installed of the airflow carding units 25a, 25b, 25c, etc., for the multistage airflow carding unit 25 is increased.

As~~[0098]~~**If a** wider carded sheet 12a is required, a ~~large number~~**plurality** of feed roll~~s~~**rolls** 13 placed in parallel may be used for the sheet. However, in the case where a shaft of the feed roll A is placed horizontally in the conventional airflow carding machine, as shown in FIG. 17 or FIG. 19, it is necessary to traverse the feed roll in the shaft direction orthogonal to its drawn out direction along with drawing out bundled fibers 12, resulting in a larger installation space per unit of feed roll **being** required. As mentioned previously, it is practically difficult to obtain the airflow carding machine with many feed rolls in parallel for the multiple spindle bundled fibers.

## SECOND EMBODIMENT

~~[0099]~~**FIGS. 5 (A) and 5 (B) are a schematic planar view and schematic frontal view diagrams** of the airflow carding machine for the multiple spindle bundled fibers, wherein use of ~~many~~**a plurality of** feed rolls makes production of a wider carded sheet possible. In FIGS. 5 (A) and 5 (B), ~~unit 10' is the supply unit~~ **10'** of the bundled fibers (filament supply unit), wherein ~~many~~**a plurality of** feed rolls 13 ~~and so on~~ are placed in the form of a matrix with each shaft being vertical. As a guide roll 14', two guide rolls 14a **and 14b** at the first stage and ~~14b~~ at the second

MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION

stage are installed according to the position of each feed roll 13 ~~and so on as to~~ differentially vary the angle of directional change ~~differentially~~ by guide rolls 14a and 14b, such as to respond to the position of the feed roll 13 and 50 on, adjusting each bundled ~~fibers~~ fiber 12 that ~~are~~ is drawn out from the second stage guide roll 14b to move in parallel and horizontally. ~~Guide~~ The guide roll 15' is made relatively long in order to guide ~~many~~ the plurality of bundled fibers 12.

[0100] As shown in FIGS. 6 (A) and 6 (B), the multistage carding unit is ~~composed of multiple placements of three~~ comprises a plurality of stage carding units 25a', 25b', and 25c' arranged in series, along the moving direction of the bundled fibers 12, as well as in parallel in a form of many units, orthogonal relative to the moving direction of bundled fibers 12 to form a sequentially integrated airflow carding machine 25'. ~~This~~ The sequentially integrated airflow carding machine 25' is equipped with long common guiding parts 252' and 253'; two common space filling guiding parts 259a and 259b placed at a certain interval between common guiding parts 252' and 253'; multiple long supporting parts 254a, 254', and 254' that are horizontally placed at certain intervals, respectively, between common guiding parts 252' in the aforementioned front end and space filling guiding part 259a, between common space filling guiding parts 259a and 259b, and between common space filling guiding part 259b and common guiding part 253' in the back end more than one ~~long~~ common guiding part 256a across three stage airflow carding units 25a', 25b', and 25c'; and dividing board 260 that separates the suction wind tunnel for airflow carding units 25a', 25b', and 25c', at each stage. Common guiding parts 252' and 253', space filling common guiding parts 259a and 259b, and supportive parts 254a, 254', and 254' can be fixed to sideboards 251 and 251', or allowed to freely ~~revolve~~ rotate, for the same reason described previously.

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

[0101] Supportive parts 254' and 254' that are placed between the space filling common guiding parts 259a and 259b<sub>2</sub> and between the space filling common guiding part 259b and the common guiding part 253'<sub>2</sub> are small in diameter<sub>2</sub> as depicted in FIG. 3 and FIG. 4. However, the supporting part 254a that is placed between the common guiding part 252' and the space filling common guiding part 259a is larger in diameter than the supporting part 254'. This configuration emphasizes an increase in carding efficiency by using a smaller diameter supportive part 254' in the first stage airflow carding unit 25a' and the second stage airflow carding unit 25b, which increases the airflow area in the wind tunnel and ~~easing~~eases the suction airflow through the bundled fibers 12, as well as between each reinforced filament of the carded sheet 12a that travels through the suction wind tunnel. In addition, because carding in the third stage airflow carding unit 25c' is fairly progressed, it mainly retains the carded sheet 12a in a horizontal position rather than increasing the carding effect.

[0102] As shown in FIG. 6 (C) ~~in an enlarged view,~~ the supportive part 254a in the third stage airflow carding unit 25c' is ~~dropped into~~ positioned in semicircular grooves 251a and 251a defined at the upper ends of sideboards 251' and 251'. Since the supportive part 254a protrudes above the tops of the sideboards 251' and 251', the carded sheet 12a that travels over ~~it~~the sideboard 251, 251', receives the carding action over the continuous wind tunnel tube without the dividing board, making the adjacent carded sheets align tightly, without a void between them, yielding a continuously aligned carded sheet.

[0103] Each common guiding part; 256a along the moving direction of the bundled fibers 12 is set up with thickness t1, t2, and t3 for the first stage airflow carding unit 25a', the second stage carding airflow unit 25b'<sub>2</sub> and the third stage airflow carding unit 25c', respectively, such as



$t1 > t2 = t3$ . Therefore, width  $w1$ ,  $w2$ , and  $w3$  between each common guiding part 256a and 256a of the moving path of the bundled fibers 12 and carded sheet 12a has a setup of  $w1 < w2 = w3$ .

[0104] In the above ~~said~~**described** carding machine for the multiple spindle bundled fibers, bundled fibers 12 are drawn out from ~~many~~**a plurality of** feed rolls 13 and so on, changing its direction by each guide roll 14' (14a and 14b), passing through guide roll 15' to be continuously carded at the first, second, and third airflow carding units 25a', 25b', and 25c' in the sequentially integrated airflow carding unit 25' and rewound around rewind roll unit 281' of the rewind roll unit 28'.

[0105] Therefore, the airflow carding machine for the multiple spindle bundled fibers, which was previously difficult to obtain, can now be accomplished. More specifically, the sequentially integrated airflow carding unit 25' has neither multistage alignment of the first stage, second stage, and third stage airflow carding units 25a', 25b', and 25c' in series, as depicted in FIG. 3, nor is the alignment of each airflow carding unit in parallel in the widthwise direction. Rather, it commonly shares the space filling common guiding parts 259a and 259b and the common guiding part 256a to construct the sequentially integrated structure, resulting in the simplification of the composition, miniaturization, weight reduction, and control of cost increases, in comparison to one with a comparable number of the sequential units in series or in parallel.

[0106] Even when the supportive parts 254' and 254a are placed horizontally, the bundled fibers 12 travel over more than one supporting part 254' and 254a placed in a small interval, applying the carding action in the conventional wind tunnel pipe stepwise at short intervals and continuously, to make carding reliable and improve the carding quality. In comparison to the case where the airflow direction is using a crescent alignment, the height of the single sequential airflow carding unit 25' ~~can be~~**is** reduced.

### THIRD EMBODIMENT

[0107] FIG. 7 shows a schematic ~~composition~~ diagram of the airflow carding machine for the multiple spindle bundled fibers, wherein ~~the multiple airflow carding machines for the multiple~~ bundled fibers are placed in a double decked alignment at certain intervals to eliminate operational shutdown during the exchange of feed rolls 13a, 13b, etc.

[0108] Namely, as the bundled fibers 12 on feed roll 13a runs out, the empty feed roll 13a is detached and a new feed roll 13a has to be put in its place, but the carding machine has to be stopped during this exchange of feed roll 13a. Since the airflow carding machine for the multiple spindle bundled fibers is equipped with many feed rolls 13a, the time required for the exchange of feed roll 13a becomes longer and the duration of machine stoppage also becomes longer. Then, in the airflow carding machine for the multiple spindle bundled fibers in FIG. 7, more than one feed unit for the bundled fibers, 10'a, . . . , 10'n, and more than one airflow carding action unit, 20'a, . . . , 20'n, and more than one rewind roll unit, 28'a, . . . , 28'n are placed in a multistage arrangement in double decked form at certain intervals.

[0109] Therefore, while bundled fibers 12 are carded by feeding the upper feed unit of the bundled fibers (filament feed unit) 10'a and in the upper airflow carding action unit 20'a, the bundled fibers 12 are also put on the lower feed unit of the bundled fibers (filament feed unit), 10'b, . . . , 10'n and in the airflow carding action unit, 20'b, . . . , 20'n. Immediately after the carding process by the upper feed unit of the bundled fibers 10'a and the upper airflow carding action unit 20'a is completed, carding of the bundled fibers 12 is initiated in the lower feed unit of the bundled fibers (filament feed section) 10'b and the lower airflow carding action unit 20'b. When the bundled fibers 12 are carded in the lower feed unit of the bundled fibers (filament feed

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

unit) 10'b, and the lower airflow carding action unit 20'b, the bundled fibers 12 are put on the upper feed unit of the bundled fibers (filament supply unit) 10'a and the airflow carding action unit 20'a. Hence, the bundled fibers 12 ~~can be~~are continuously carded.

[0110] As the number of upper and lower stages has more surplus, the bundled fibers 12 can be ~~carded-simultaneously~~ carded on more than one feed unit of the bundled fibers (filament feed unit) 10' and the airflow carding action units 20'. It is also possible that both an upper stage and a lower stage setup are set in combination and alternately operated, to card bundled fibers in every other spindle and rewind around a rewind roll the carded reinforcing filaments that are carded in every other spindle, without a void existing between them, continuously producing a carded sheet.

[0111] In the embodiment ~~of~~shown in FIG. 7, an example wherein the bundled fibers 12 and the carded sheet 12a travel horizontally from the left end of the figure to rewind around the rewind roll unit 28 at a right end, is described. It is also possible that at least the airflow carding units 25'a and 25'b are vertically placed such that the bundled fibers 12 travel from top to bottom in one unit, then travel from bottom to top in another, changing the moving direction of the bundled sheets 12a and 12b sent from the upper and lower airflow carding units 25'a and 25'b by 90 degrees. By changing the direction of roll so that it travels horizontally, a pair of carded sheets 12a and 12b in parallel can be aligned to yield a single wide carded sheet. Alternatively, each reinforcing filament for the carded sheet 12a and that of the carded sheet 12b are alternately placed in the odd and even number positions, respectively, to produce a wide carded sheet.

#### FOURTH EMBODIMENT

[0112] In the above discussed embodiment, the case, wherein more than one supportive part 254, 254', and 254a in the airflow carding units 25, 25a, 25b, 25c, 25'a, 25'b, and 25'c are placed in a plane and arranged horizontally along the moving direction of the bundled fibers 12 and carded sheet 12a, is described. However, as shown in FIG. 8, multiple supporting parts 254 can be placed in a convex crescent form against the airflow direction. The airflow carding unit with convex placement of ~~this~~the supportive unit can be a single carding machine for the bundled fibers, as shown in FIG. 1, a multistage airflow carding machine, as shown in FIG. 3, a multistage multiple sequential airflow carding machine, as shown in FIG. 5, or a double decked multistage carding machine for the multiple spindled bundled fibers, as shown in FIG. 7. In these cases, it is possible that the tension of the feed roll 13 and the rewind tension can properly be adjusted by the tension applying means 16 and the rewind roll unit 28, respectively, transforming the bundled fibers 12 and carded sheet 12a into a convex crescent form along multiple supportive parts that are placed in a crescent form. As in the case where more than one supportive part is placed horizontally, the fiber height detection unit, the upstream feed roll, and the downstream feed roll ~~can also be~~is not necessary and omitted.

#### FIFTH EMBODIMENT

[0113] As shown in FIG. ~~8 mentioned above,~~8, it is possible to place more than one supportive part 254 in a crescent form, where if necessary, an upstream feed roll unit 23 can be placed downstream of the guide rolls 21 and ~~22~~22, as shown in FIG. 9. Downstream of ~~this~~the feed roll unit 23, namely upstream of the airflow carding unit 25, the fiber height detection unit 24 can be

placed, or downstream of the fiber carding unit 25, the downstream feed roll unit 26 and the fiber height detection unit 27 can be placed.

[0114] Since the upstream feed roll unit 23 and the downstream feed roll unit 27 have the same composition, the upstream feed roll unit 23 will be described as an example. As shown in FIG. 10, the feed roll unit is comprised of the drive roll 231, freely revolving ~~roll~~rolls 232 and 233, guide rolls 234 and 235, retaining part 236, and air cylinder 237. The drive roll 231 is driven by a driver motor, which cooperates with the freely ~~revolving~~rotating rolls 232 and 233 to draw out the bundled fibers 12. Guide rolls 234 and 235 feed the bundled fibers 12 from a certain direction to the space between the ~~said~~-drive roll 231 and the freely ~~revolving~~rotating rolls 232 and 233. Retaining part 236 holds the ~~said~~-freely ~~revolving~~rotating rolls 232 and 233 and air cylinder 237 as an actuator to raise or lower ~~this~~the retaining part 236, and raising and lowering of the ~~said~~-holding part by the piston rod 238 of the air cylinder 237 applies a required load to the freely ~~revolving~~rotating rolls 232 and 233 against the drive roll 231 to send the bundled fibers 12 12 downstream.

[0115] Fiber height detection units 24 and 27 have the same ~~composition~~structural configuration and the fiber height detection unit 24 will be described herein as a ~~representation~~an example. As shown in FIG. 11, the fiber height detection unit 24 is equipped with a pair of fixed or freely ~~revolving~~rotating guide rolls 241 and 242 that are placed before and after the moving direction of the bundled fibers 12 at a certain interval to move the bundled fibers 12 over ~~these~~the guide rolls 241 and 242. Then, the bundled fibers 12 that have been sent by the feed roll unit 23 under an overfed condition, is bent into a crescent form by the airflow between guide rolls 241 and 242, where the level of the bending of the bundled fibers is detected by a photoelectric or displacement sensor 243.

[0116] While the carding machine for single bundled fibers shown in FIG. 9, mentioned above, performs essentially the same carding action as the carding machine for the single bundled fibers depicted in FIG. 1, functional differences in the installation of the upstream feed roll unit 23, the fiber height detection unit 24, the downstream feed roll unit 26, and the fiber height detection unit 27 will now be described. The mass that is fed by the upstream feed roll unit 23 is set slightly larger than that by the downstream feed roll unit 26, leading to an overfed condition. Therefore, the bundled fibers 12 can be bent as much as the overfed mass in the fiber height detection unit 24 and the multistage carding machine unit 25. The bent condition in the fiber height detection units 24 and 27 can be stabilized by the action of the suction system or through lightweight superposition.

[0117] The fiber height detected by the fiber height detection unit 24 is sent to the drive roll 231 of the feed roll unit ~~23~~23, as shown in FIG. 10, ~~whereby~~wherein starting or stopping the drive motor allows for the adjustment of the mass of the fed bundled fibers ~~12 fed~~12, optimizing the overfed mass to a proper amount.

[0118] The fiber height of the carded sheet 12a that is detected by the fiber height detection unit 27 is sent to the driver motor of the rewind roll unit 28 to adjust the rewind tension of the carded sheet 12a by rewind roll unit 28 ~~at~~to be constant. This eliminates pitching of the carded sheet 12a that is rewound to yield a roll of high quality carded sheet 12a.

## SIXTH EMBODIMENT

[0119] As shown in ~~FIG. 12~~FIGS. 12 (A) and 12 (B), the carding machine for the multiple spindle bundled fibers can have an upstream feed roll unit 23', a fiber height detection unit 24', and a downstream feed roll unit 26'.

[0120] As shown in FIG. 13 (A), the upstream feed roll unit 23' ~~is composed of~~ includes a relatively long common drive roll 231', ~~many~~ a plurality of separate, freely revolving rotating rolls 232 for each bundled fibers 12, and ~~many~~ a plurality of separate air cylinders 237 separate, freely revolving rotating rolls 232. When the overfed amount of the bundled fibers 12 is ~~large~~ substantial, as shown in FIGS. 13 (A) and 13 (B), each separate freely revolving rotating roll 232 is raised by each separate air cylinder 237 to temporarily stop the feeding of the bundled fibers 12. As the amount of overfed mass becomes a proper value, as shown in FIG. 13 (C), each separate air cylinder 237 pushes down each separate freely revolving rotating roll 232 in cooperation with the drive roll 231' to independently draw out the bundled fibers 12.

#### SEVENTH EMBODIMENT

[0121] As shown in FIG. 14, the double decked multistage carding machine for the multiple spindle bundled fibers can be equipped with an upstream feed roll unit 23'a and the fiber height detection unit 24'a to replace the guide roll 15 or be used in conjunction with the guide roll 15.

[0122] FIGS. 15 (A) and 15 (B) show ~~other embodiments with a structure of the~~ a supportive part in the carding machine for the multiple spindle bundled fibers in accordance with the present invention. As described in FIG. 3, FIG. 4, and FIG. 6, a structure of ~~more than one~~ a plurality of supportive ~~part~~ parts 254 and 254' in the airflow carding units 25 and 25' has a drilled hole through the sideboard 251, spacer 255, and guide part 256. Support parts 254 and 254' are inserted into ~~this~~ the hole. However, it is complicated to insert many small diameter supporting parts 254 and 254' into many small diameter drilled holes.

[0123] Then, in the airflow carding unit 25" in the embodiment shown in FIGS. 15 (A) and 15 (B), the top of the sideboard 251 is cut to form ~~more than one slit~~ a plurality of slits 251b

**MARKED-UP COPY  
OF SUBSTITUTE SPECIFICATION**

~~to~~having a certain depth and the supporting part 254 is inserted into ~~this~~the slit 251b. In ~~this~~the support structure, in which the supporting part 254 is inserted into the slit 251b, assembly of the supporting part 254 with the sideboard 251 is much easier and can be completed within a short time of period as compared to insertion of the supportive part 254 into the drilled hole.

[0124] In the support structure where the supportive part 254 is inserted into the slit 251b, as ~~required and shown in the figure~~, a female screw 251c is drilled into ~~both tops~~the top surface of the sideboard 251, which is covered with an approximately U-shaped cap 260 that is tightened with a screw 261. A flat plate 260a, a downward vertical plate 260b that hangs from both ends, and a drilled hole 260c are located such that they match up with the female screw 251c of the aforementioned flat plate 260a. This arrangement prevents the supportive part 254 from rising in the slit 251b and dropping from the slit 251b.

[0125] The embodiment of FIGS. 15 (A) and 15 (B) shows only the sideboard 251. However, as described previously, as spacer 255 and guiding part 256 are used together with the sideboard 251, a slit can be cut at the same pitch and depth into spacer 255 and guiding part 256 as in sideboard 251, so that the supporting part 254 can be inserted into ~~this~~the slit. If required, sideboard 251, spacer 255 and guiding part 256 are covered with ~~said~~the similar cap 260 and then tightened with the screw.

[0126] In the above embodiment, it was described that the sideboard 251 is cut to form a deep slit, 251b, and the supporting part 254 is supported at a lower position than the top of the sideboard 251. ~~It is acceptable that~~The sideboard 251 ~~is~~can be cut to form a shallow slit and the upper part of the supporting part 254 is supported at the same height as the top of sideboard 251. In this case, the cap 260 can be a flat plate.



[0127] In the above embodiment, it was described that the supporting part 254 is placed ~~in a plane and horizontally~~ in a plane, similar to those in FIG. 4 and FIG. 6. However, similar to the case in FIG. 8, the cut of each slit can be in a crescent form so that the supporting part 254 can be inserted in a crescent form.

[0128] In the above embodiment, a temperature of the air stream flowing into the airflow carding unit 25 through the wind tunnel is not specifically described. However, depending on the kind of adhesive (sizing agent) sticking to each reinforcement filament in the airflow carding machine having a single or multistage airflow carding unit as shown in FIG. 16 (A), a hot air suction wind tunnel can be created in the airflow carding unit where hot air 270 can weaken the adhesion force of the adhesive (sizing agent) and promote the carding action.

[0129] In the above embodiment, it has been described that the guiding part and supportive part are solid. However, as shown in FIG. 16(B), the guiding parts 252 and 253 and/or the supportive part 254 can be a pipe and ~~these~~ the pipe-shaped guiding parts 252 and 253 and/or supportive part 254 can be equipped with a built-in cartridge heater 272 in a hollow pipe 271 to heat the guiding parts 252 and 253 and/or the supportive part 254. In this setup, the bundled fibers and/or carded sheet is properly heated by the guiding parts 252 and 253 and supportive part 254 that is heated by the cartridge heater 272 to heat and soften the sizing agent in the bundled fibers, reducing the bonding force to generate a smoother carding action.

[0130] As shown in FIG. 16C, the guiding parts 252 and 253 and/or the supportive part 254 is pipe-shaped and ~~its~~ has a hollow ~~inside~~ interior 271 can be run with heated fluid 273, such as hot air, steam or hot water can be run. In this setup, the guiding parts 252 and 253 and/or the supportive part 254 is heated by the heated fluid 273 that flows in the pipe and properly heats the

bundled fibers and/or carded sheet to heat and soften the sizing agent in the bundled fibers and weaken the bonding force to generate a smoother carding action.

[0131] In the carding machine for the multiple spindle bundled fibers, as shown in FIG. 16(D), the guiding parts 252 and 253 and/or supportive part 254 in the final stage of the airflow carding unit have a pipe shape and a slit 274 is ~~cut~~**defined** in the part of the pipe-shaped guiding parts 252 and 253 and/or the supportive part 254 where the slit 274 crosses in the moving direction of the carded sheet. Then, the heated air 275 is run inside of the hollow pipe 271 of the guiding parts 252 and 253 and/or the supportive part 254, ejecting the hot air through slit 274 towards the carded sheet 12a. Due to a cooling sizing agent, this leads to the carding of the reinforced filament forming the carded sheet 12a in a uniform interval.

[0132] More than one of ~~examples in the embodiment~~**the exemplary embodiments** of the present invention are described above, but the present invention is not limited by these examples ~~of the embodiment~~. The present invention is intended to include the embodiment comprising the description within the spirit and ~~claim~~**appended claims** of the present invention. For example, while it is described in each embodiment that thickness,  $t$ , in spacer 255 and guiding part 256a can be varied stepwise, it can also be continuously varied along the moving direction of the bundled fibers 12 or carded sheet 12a to continuously increase the width,  $w$ , of the traveling path for the bundled fibers 12 or carded sheet 12a in a downstream direction.

[0133] Or depending on the kind of bundled fibers 12, the distance between the sideboards 251 and 251' of the frames 250 and 250' can continuously fan out towards the moving direction of the bundled fibers 12 or carded sheet 12a to continuously increase the width of the traveling path,  $w$ , for the bundled fibers 12 or carded sheet 12a.

[0134] Furthermore, it is described in the embodiment shown in FIG. 4 that more than one supporting part 254 is placed ~~in a plane and horizontally~~ in a plane in each airflow carding units 25a, 25b, and 25c. It is also described in the embodiment of FIG. 6 and FIG. 7 that more than one supportive part 254a and 254' is placed ~~in a plane and horizontally~~ in a plane in the multistage sequential airflow carding units 25' and 25'a. However, ~~these~~the supporting parts can be placed in a plane and either tilted upwards or downwards along the moving direction of the bundled fibers 12 in a single or multistage airflow carding unit.

[0135] In the above embodiment, an airflow wind tunnel using suction airflow was described, but airflow that is blown can also be used.

[0136] Furthermore, in the above embodiment it is described that the guiding parts 252, 253, 252', and 253', the space filling common guiding parts 259a and 259b, and the supporting parts 254, 254a, and 254', are all cylindrical, namely having a constant diameter regardless of the length of the direction. However, ~~these~~the parts can have a large diameter at both ends in the length direction and a smaller diameter that gradually decreases towards the middle, creating a hand drum shape of the guiding ~~parts~~ and supporting parts. Use of these guiding ~~parts~~ and supportive parts can reduce the difference in the distance between the center axis line of the single fiber of the bundled fibers 12 and the reinforced filament at both ends of the carded sheet 12a to apply a large tension force to the reinforced filament at both ends in the carded sheet 12a, as compared to using the cylindrical guiding ~~parts~~ and supportive parts.

[0137] In the above embodiment, it was described that multiple supportive parts are used in all cases. However, at least one or more supportive parts are acceptable and a single supportive part can be used. In this case, the carding effect in the bundled fibers 12 and carded sheet 12a is lowered and stabilization of its configuration tends to be more difficult, as compared to the case

when more than one supporting part is used. However, as compared to the case in the airflow carding unit without a single supportive part, the carding action occurs before and after the supporting part to lead not only to substantially smoother carding action, but also to stabilize the configuration of the bundled fibers and/or carded sheet because the bundled fibers and/or carded sheet is supported by the supporting part. Both the tension applying means and the tension applied by the rewind roll to bundled fibers 12 and carded sheet 12a can further stabilize the bundled fibers 12 and the carded sheet 12a even if the support is performed by a single supporting part.

[0138] Furthermore, it was described in the above embodiment that the tension applying means 16 is placed on each feed roll 13. However, each feed roll 13 can ~~revolve~~rotate in reverse and instantly apply tension to the bundled fibers 12. For example, it is possible that a pulley be installed on the shaft of each feed roll 13 and placed with a belt working as a driving force that delivers means for a single driver motor to revolve the roll under low tension in the opposite direction of the bundled fibers 12, resulting in ~~the~~ application of an overall constant desired tension to multiple bundled fibers 12. A fact that tension is always applied to the bundled fibers 12 prevents the bundled fibers 12 from loosening and keeps them stretched, when the carding process is temporarily stopped. When the carding process is restarted, the initial setup for the bundled fibers can almost be omitted. Application of a required tension to many bundled fibers 12, on the whole, can possibly keep costs down.

[0139] The airflow carding machine for the bundled fibers in the present invention is comprised of a feed roll wound with the bundled fibers; the airflow carding unit to card the bundled fibers drawn out from this feed roll with the airflow orthogonal ~~in~~relative to the moving direction of the bundled fibers; and the rewind roll to rewind the carded sheet that is carded in

the airflow carding unit. Since the said airflow carding unit is characterized by having more than one supportive part that is placed at a certain interval along the moving direction of a single or multiple bundled fibers, the carding action of the bundled fibers and carded sheet that travels over a single supportive part or multiple supportive parts in a short distance is applied. This is either applied, at a minimum, twice before and after the supporting part as the carding action of the conventional wind tunnel tube, or stepwise and continuously to make the carding reliable and of better quality.

[0140] Furthermore, since the configuration of the bundled fibers or carded sheet is always kept constant along the supporting part of the airflow carding unit, it becomes unnecessary to have a front feeder upstream of the airflow carding unit, or a fiber height detection unit in the airflow carding unit to feedback the fiber height detected to the driver motor for the drive roll of the front feeder to adjust for the overfed condition. Therefore, not only are the number of various component parts, such as the fiber height detection unit, the front feeder, and its driver motor reduced to save parts cost, but also the installation space for these components becomes unnecessary, simplifying the composition to achieve miniaturization, weight reduction and lower cost.

[0141] The above effect becomes more pronounced with the increase in the number of stages, as multiple airflow carding units are placed in multistage along the moving direction of the bundled fibers. Furthermore, when the width of the traveling path of the carded sheet in more than one airflow carding unit is increased stepwise or continuously downstream in the moving direction of the carded sheet, an orderly response to the increase in width of the bundled fibers and carded sheet, along with carding of the bundled fibers and carded sheet in the airflow carding unit, achieves smooth continuous carding.

[0142] In the present invention, as the shaft of the feed roll of the bundled fibers is placed in the vertical direction, even if the feeding position of the bundled fibers that are drawn out from the feed roll is altered vertically, there is little variation in the supply position in relation to the airflow carding action unit so that the feed roll is not required to traverse towards its shaft direction as in a conventional airflow carding machine where the shaft of the feed roll is placed in a horizontal direction. This can reduce the required installation space for the feed roll and achieve feeding of more than one bundled fibers in the airflow carding machine for the multiple bundled fibers, which was previously difficult to achieve.

[0143] In the above embodiment, a simple airflow carding machine was described in all cases. However, the carding machine in the present invention can be used when the carding machine is based on fluids, such as water or oil.

#### ~~INDUSTRIAL APPLICABILITY~~

[0144] The carding machine for the bundled fibers in the present invention can easily and reliably card the bundled fibers collected from many reinforcing filaments to manufacture a carded sheet. ~~The carded sheet that is manufactured accordingly can be used as the fiber reinforced composite material impregnated into a matrix; it has broad application in aerospace, land transportation, shipping, building, construction, industrial parts, and sporting goods.~~